



ISO-9001:2008

AUTOMOTIVE SOLUTIONS™



Regd. Office : 11/9, Ground Floor, Old Rajinder Nagar
New Delhi - 110060, INDIA.



Sales Office : WZ-75A, Toda Pur,
New Delhi - 110012.



Customer Support :
011-329 37026, 011-470 37026.



www.automotivesolutions.net.in



www.buypaintsonline.com



info@automotivesolutions.net.in

QUALIFIES ASTM STD

MIL Paints

AS PER- SPECS
FED-595 / RAL / BS

Material Safety Data Sheet

1. Hazards Identification

Route of entry:	1&2	May cause allergic skin response in certain individuals. May cause moderate irritation to the skin such as redness and itching.
Skin contact		
Skin absorption	3)	May cause irritation.
Eye contact	4)	If product is heated, vapors generated can cause headache, nausea, dizziness and possible respiratory irritation if inhaled in high concentrations
Inhalation		
Ingestion	5)	Low acute oral toxicity.

Emergency Overview WARNING May cause skin irritation. May cause eye irritation. May cause allergic reaction. Clear, viscous liquid with mild odor.

WHMIS Symbols

Potential Health Effects As above



2. Handling and Storage

Handling Procedures and Equipment Avoid prolonged or repeated skin contact. Wash thoroughly after handling. Launder contaminated clothing before reuse. Avoid inhalation of vapours from heated product. Precautionary steps should be taken when curing product in large quantities. When mixed with epoxy curing agents this product causes an exothermic, which in large masses, can produce enough heat to damage or ignite surrounding materials and emit fumes and vapours that vary widely in composition and toxicity.

3. Storage Requirements

Store in cool, dry place. Store in tightly sealed containers to prevent moisture absorption and loss of volatiles. Excessive heat over long periods of time will degrade the product.

4. First Aid Measures

Skin Contact	Remove contaminated clothing. Wipe excess from skin. Apply waterless skin cleaner and then wash with soap and water. Consult a physician if effects occur
Eye Contact	Flush immediately with water for at least 15 minutes. Consult a physician.
Inhalation	Remove to fresh air if effects occur.
Ingestion	No acute adverse health effects expected from amounts ingested under normal conditions of use. Seek medical attention if a significant amount is ingested.





ISO-9001:2008

AUTOMOTIVE SOLUTIONS™



Regd. Office : 11/9, Ground Floor, Old Rajinder Nagar
New Delhi - 110060, INDIA.



Sales Office : WZ-75A, Toda Pur,
New Delhi - 110012.



Customer Support :
011-329 37026, 011-470 37026.



www.automotivesolutions.net.in



www.buypaintsonline.com



info@automotivesolutions.net.in

QUALIFIES ASTM STD

MIL Paints

Material Safety Data Sheet

AS PER- SPECS
FED-595 / RAL / BS

5. Exposure Control/Personal Protection

Exposure Limits

ACGIH TLV

Not established for product as whole. Refer to OSHA's Permissible Exposure Level (PEL) or the ACGIH Guidelines for information on specific ingredients.

OSHA PEL

As above

Other (specify)

EYE PROTECTION GUIDELINES:

Safety glasses with side shields or chemical splash goggles.

SKIN PROTECTION GUIDELINES:

Wear liquid-proof, chemical resistant gloves (nitrile-butyl rubber, neoprene, butyl rubber or natural rubber) and full body-covering clothing.

RESPIRATORY/VENTILATION GUIDELINES:

Good room ventilation is usually adequate for most operations. Wear a NIOSH/MSHA approved respirator with an organic vapour cartridge whenever exposure to vapour in concentrations above applicable limits is likely.

6. Engineering Controls (specific)

General

Local Exhaust

Other (specify)

Practice good caution and personal cleanliness to avoid skin and eye contact. Avoid skin contact when removing gloves and other protective equipment. Wash thoroughly after handling. Generally speaking, working cleanly and following basic precautionary measures will greatly minimize the potential for harmful exposure to this product under normal use conditions.

Transport Information

DOT Non-Bulk

IMDG

SHIPPING NAME:

Environmentally hazardous substance, liquid, n.o.s.

TECHNICAL SHIPPING NAME: Paint.

HAZARD CLASS: Class 3.

U.N. NUMBER: . UN 1263

PACKING GROUP: PG III.

EmS Number: ..F-A, S-F

MARINE POLLUTANT Yes

ICAO/IATA

SHIPPING NAME: Environmentally hazardous substance, liquid, n.o.s.

TECHNICAL SHIPPING NAME: Paint.

HAZARD CLASS: Class B.

U.N. NUMBER: UN3082.

PACKING GROUP: . PG III.

MARINE POLLUTANT: Yes

FOLLOW US ON :

