



AUTOMOTIVE SOLUTIONS

(ISO-9001:2008 CERTIFIED COMPANY)

EPOXY FLOORING : METAL COATINGS : WALL COATINGS : WATERPROOFING : PAINT : NON PAINT PRODUCTS.

Office : 11/9, Ground Floor, Old Rajinder Nagar
New Delhi - 110060, INDIA.

Mobile : (+91) 93500 42380, 93100 37026

Customer Support : 011-470 37026, 329 370 26

E-mail : automotive_solutions2000@yahoo.co.in

Website : WWW.AUTOMOTIVESOLUTIONS.NET.IN

PRODUCT LITERATURE

OIL REMOVER - CLEANER & DEGREASER

Product Description:

Our multi-purpose Oil Cleaner & Degreaser is used to remove any kind of dirt, oil & grease from the surface. At times spilled Oil & Grease can lead to accidents by making floor slippery or may aggravate fire or loss of life.

Intended Uses:

- Degreasing concrete floors, gutters, walls and greasy/oily equipment.
- Quickly cuts through grease, industrial soils and petroleum-based liquid products.
- Ideal for cleaning and degreasing of metal surfaces before coating.
- Cleaning of oily concrete floors
- Cleaning of car engines, generators
- Food industry floor cleaning

Features & Benefits:

- Water Based
- Easy to use
- Non - Abrasive
- Bio-degradable
- Non Toxic
- Non - Flammable
- Environment friendly
- Phosphate free
- Safe & fast cleaning
- Agitates to remove Oil, Grease & Stains Instantly
- Neutral in pH
- Hypoallergenic
- Confirms IS Standards



Product Information:

Appearance	Transparent
Color	Greenish
Form	Liquid
Flash Point	Not Applicable
pH	6.8 – 7
Solubility in Water	Soluble
Specific Gravity	@ 25°C: 1.00 gm/cc
Flammability	Not Flammable

Application details:

Shake well before use. Recommended dilution ratio for Degreaser: Water

	Ratio Oil Remover / Water
<i>General purpose degreasing</i>	<i>1:8</i>
<i>Heavy Cleaning for Oil & Grease</i>	<i>1:4</i>
<i>Engine parts, industrial equipment</i>	<i>1:4</i>

Solutions can be adjusted to specific cleaning needs.

Method:

Substrate - Brush, Hand sprayer, pump-style garden sprayer or chemical applicator.

Storage & Packaging

Store away from Direct Sun, Heat and Severe Cold.

Packaging: 1Ltr, 5 Ltr. 10 Ltr and 20 Ltr

Application

- *Before use conduct a small test patch for suitability of product to the substrate.*
- *Coat all surfaces with CLEANER & DEGREASER using a cloth, sponge, brush, mop.*
- *Wait 1 - 5 minutes for product to penetrate grease and dirt. Allow product to be in contact with the surface longer (up to 20 minutes) if you have difficult areas/parts to clean. Agitate or scrub if necessary*
- *Wash using a cloth, brush, mop, sponge, hose or pressure washer and rinse area thoroughly with clean water.*
- *Wash vertical surfaces from top to bottom*